



Pos.	Description	Material, Type	Size
1	Cover	Ductile iron	DN500, 40t
2	Service opening, insulated	PE	D700
3	Tank cylinder, double wall	PE100	ID700, SN2, L1515
4	Lifting chain	AISI316	3 mm
5	Cable inlet pipe	PE100	D50 SDR17
6	Auto-coupling	Ductile iron, epoxy coating	DN50, 2"
7	Non return valve, NBR ball	Ductile iron, epoxy coating	DN50, 2"
8	Ball valve	PPGF/PE100	DN50, 2"
9	Pressure pipe	AISI316	DN50, 2", L785
10	Outlet pipe	PE100	D63 SDR17
11	Inlet pipe	PE100	D160 SDR33
12	Pump - KSB Ama-Porter50_SE1-230V	with floating switch	H <sub>max</sub> =9,7m, Q <sub>max</sub> =20m <sup>3</sup> /h
13	Bottom	PE100	20 mm
14	Bolts, nuts, washers	AISI316	M8, M16
15	Alarm device Tank-Check RF-412	Optional	<input type="checkbox"/> YES / NO <input type="checkbox"/>

Drawn:	A.Käärid	<b>Pumping Station ID700 STRONG</b> Iron cover / KSB AmaPorter50_SE		
Approved:	J.Karolin			
www.iwsgroup.ee		Mass: kg	Product code:	Rev.
<b>Innovative Water Systems</b>		<b>~170</b>	<b>500706</b>	<b>0</b>