



Pos.	Description	Material, Type	Size
1	Cover, insulated	PE	D700
2	Service opening, insulated	PE	D700
3	Tank cylinder, double wall	PE100	ID1000, SN2, <b>L2065</b>
4	Lifting chain	AISI316	3 mm
5	Cable inlet pipe	PE100	D50 SDR17
6	Auto-coupling	Ductile iron, epoxy coating	DN40, 1 1/2"
7	Non return valve, NBR ball	Ductile iron, epoxy coating	DN40, 1 1/2"
8	Ball valve	PPGF/PE100	DN40, 1 1/2"
9	Pressure pipe	AISI316	DN40, 1 1/2", <b>L785</b>
10	Outlet pipe	PE100	D50 SDR17
11	Inlet pipe	PE100	D160 SDR33
12	Pump - Wilo MTC40F16.15/7/1-230V	with floating switch	H <sub>max</sub> =16m, Q <sub>max</sub> =15m <sup>3</sup> /h
13	Bottom	PE100	20 mm
14	Bolts, nuts, washers	AISI316	M8, M16
15	Alarm device Tank-Check RF-412	Optional	<input type="checkbox"/> YES / NO <input type="checkbox"/>

Drawn:	A.Käärid	<b>Pumping Station ID1000 STRONG</b> Plastic cover / Wilo MTC40			
Approved:	J.Karolin				
<b>Innovative Water Systems</b>		www.iwsgroup.ee	Mass: kg	Product code:	Rev.
		~230	500901	0	