



Pos.	Description	Material, Type	Size
1	Cover	PE / Cast iron	according to selection
2	Handrail, telescopic, HAILO	AISI316	270x1620
3	Service opening	PE	according to selection
4	Ladder, non slippery steps, HAILO	AISI316	300x340
5	Tank cylinder, double wall	PE100	ID1400, SN4
6	Backing ring	PP - Steel	according to selection
7	Gate valve, AVK	Ductile iron, epoxy coated	according to selection
8	Flanged tee	Ductile iron, epoxy coated	according to selection
9	Tensile combi-flange	Ductile iron, epoxy coated	according to selection
10	Pressure pipe	PE100	according to selection
11	Bottom	PE/Concrete	155 mm
	Bolts, nuts, washers	AISI316	according to selection

640x1100 cover PE (insulated)

A

DN800 cover cast-iron 40t
Ø800 free opening

B

Ø795 cover PE (insulated)

C

DN600 cover cast iron 40t

D

Ø 630

Service opening type	A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input type="checkbox"/>
Handrail, telescopic (not available for type "B")	<input type="checkbox"/> YES / NO <input type="checkbox"/>
Pressure pipe depth from Ground Surface	H = mm
Pressure pipe 1 diameter	D1 = mm
Pressure pipe 2 diameter	D2 = mm
Pressure pipe 3 diameter	D3 = mm

Drawn:	E.Ehala	Valve chamber ID1400 STRONG
Approved:	J.Karolin	

www.iwsgroup.ee	Mass: kg	Product code:	Rev.
Innovative Water Systems	NA	505215 / ordersheet	3