



Pos.	Description	Material, Type	Size
1	Cover	PE / Cast iron	according to selection
2	Handrail, telescopic	AISI316	270x1620
3	Service opening	PE	according to selection
4	Ladder, non slippery steps	AISI316	300x280
5	Tank cylinder, double wall	PE100	ID2000, SN4
6	Backing ring	PP - Steel	according to selection
7	Gate valve, AVK	Ductile iron, epoxy coated	according to selection
8	Flanged tee	Ductile iron, epoxy coated	according to selection
9	Tensile combi-flange	Ductile iron, epoxy coated	according to selection
10	Pressure pipe	PE100	according to selection
11	Anchor bolt W-FA	AISI316	M20x150, 12 pcs
12	Bottom, steel reinforced	PE100 - Steel	155 mm
13	Concrete plate, reinforced	Concrete	200x2800x2800
	Bolts, nuts, washers	AISI316	according to selection

895x1470 cover PE(insulated)

A

DN800 cover cast-iron 40t  
Ø800 free opening

B

Ø795 cover PE (insulated)

C

DN600 cover cast iron 40t

D

Service opening type		A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input type="checkbox"/>	
Handrail, telescopic (not available for type "B")		<input type="checkbox"/> YES / NO <input type="checkbox"/>	
Pressure pipe depth from Ground Surface		H =	mm
Pressure pipe 1 diameter		D1 =	mm
Pressure pipe 2 diameter		D2 =	mm
Pressure pipe 3 diameter		D3 =	mm

Drawn:

K.Käbi

Approved:

Valve chamber ID2000 STRONG

www.iwsgroup.ee

Mass: kg

Product code:

Rev.

Innovative Water Systems

NA

505225 / ordersheet

3